

***** DRAFT – NOT FOR FILING *****

3745-512-630

Cap system collection pipes and outlets.

(A) Cap system collection pipes and pipe outlets shall meet the following criteria:

(1) Be permanently fused together.

(2) If perforated, shall not be wrapped with filter fabric.

(B) The owner or operator shall surround cap system collection pipes with material to protect the pipes from crushing, deflection, and deformation. The surrounding material shall meet the following criteria:

(1) Contain particles with dimensions that will not clog any pipe perforations

(2) Not be wrapped with filter fabric.

(C) Materials used by the owner or operator for cap system collection pipes, cleanout access, and pipe outlets shall meet the following criteria:

(1) Be resistant to crushing and deformation under the expected maximum loads and settlement.

(2) Not consist of corrugated metal.

(D) Certification of the cap system collection pipes by the owner or operator shall include the following:

(1) Record drawings of the pipes showing the location of the pipes in plan view, the slope of the pipes, and the elevation of the pipe invert at the ends of each run of pipe, as constructed.

(2) Record drawings showing the locations, plan views, and elevations of the cleanout access and outlets.

(3) Drawings showing the details of the cleanout access and outlets, as constructed.

(4) Results of all testing and verification that the cap system collection pipes meet the standards in paragraphs (A) to (C) of this rule and the specifications in the authorizing document.